



**Tehnički podaci :**

Napajanje	115/230 V, 50-60 Hz
Snaga	550 W max / 100 W at 1/8 output power
Frekvencijski raspon	20 – 20.000 Hz +/-1 dB
Omjer signala i šuma	R>98 dB, A-weighted
Distorzija	< 0,05 %
Pojačanje po kanalu	- 100 dB, 1 dB korak
Digitalna Obrada Signala	Integrirana, 48 kHz, 24 bit – 344 MIPS
<i>FlexNet / Cobranet</i>	2 x FlexNet redundant (automatic switching)/ Cobranet, Ethernet 10/100 Mbits. Female RJ-45
Linijski audio izlazi	5 x balanced audio 1 Vp, 0,707 Vrms. 10 K $\Omega$ , 3 Pin, Euroblock type
LDA ACSI sabirnica	1 x balanced audio 1 Vp, 0,707 Vrms. 10 K $\Omega$ , Female RJ-45, total 800 m / 2624.7 ft
Izlazi predpojačala	8 x balanced audio 1 Vp, 0,707 Vrms. 100 $\Omega$ , 3 Pin, Euroblock type
Snimanje zvuka /kontrolirani izlazi	1 x balanced audio, 1 Vp, 0,707 Vrms. 100 $\Omega$ / 0 – 5 V DC output 100 $\Omega$ , 4 Pin, Euroblock type
ATT kontrola	8 x override 24 V DC, 8 x 40 mA, 2 Pin, Euroblock type (4 pin connector)
Kontrolni ulazi za nuždu	10 x 0 – 5 V DC, monitored inputs, 2 Pin, Euroblock type (4 pin connector)
Kontrolni izlazi za nuždu	2 x relay contact isolated output, NO, max 60 V DC 130 mA, 2 Pin Euroblock type (4 pin connector)
GPIO	14 x Control I/O, 0 - 5 V, 100 $\Omega$ , 3 Pin, Euroblock type
Virtualna matrica	32 x 1024
Pojačala	8 x 120 W Class D, 60 Wrms x 8 @ 70 / 100 V. Min load 166 $\Omega$ or 4 x 250 W Class D, 120 Wrms x 4 @ 70 / 100 V. Min load 83 $\Omega$
Zvučnički izlazi	16 (8 dual managed lines) x 70/100 V. 2 Pin, Euroblock type (4 pin connector)
Zvučnički loop ulazi	16 (8 dual) x no voltage contact, 3 Pin, Euroblock type

Rezervni ulazi za pojačala	8 x 60 Wrms at 70 or 100 V, 2 Pin, Euroblock Type (4 pin connector)
Zaštita	Over-temperature, DC, infrasonic, short circuit, slow start-up, overload, start-up test
Emergency power input	1 x 20 - 25V DC, 20A, fused, 2 Pin, Euroblock type
Emergency power status inputs	3 x NO - NC, 3 Pin, Euroblock type
Ekran	TFT 480x272 4,3" with Touch Panel
Uvjeti radne okoline	-5 °C to +45 °C / 23 °F to 113 °F 5% to 95% Relative humidity (no condensation)
Izvedba kućišta	Front: Fe, Grey RAL 7016 Back: Fe, Black RAL 9005 Case: Al, Black RAL 9005
Težina	13.5 kg / 29.76 lb
Dimenzije (W x H x D)	483 mm x 88 mm x 455 mm / 19" x 3.46" x 18"
Dodaci	2 x rack mounting, male Euroblock connectors, installation screws, 4 x rubber foot, 1 x power cable 2 m / 6.56 ft (EU Type), 1 x Ethernet cable 2 m / 6.56 ft

